

PRODUCT INFORMATION



Lubricants – Greases

Version: 620/02

Valvoline™ Multipurpose Calcium 2

Conventional calcium grease with good water resistance properties. Suitable for lubrication of machinery working in damp conditions.

Valvoline Multipurpose Calcium 2 is a Calcium thickened lubricating grease formulated with naphthenic base oil and enhanced with a green color to enable easy verification on applied parts. The product protects against rust and corrosion especially in marine and agriculture applications where water resistance is needed.

Performance levels

DIN 51502:	K2E-30
------------	--------

Applications

Suitable for use in normal temperature conditions.

Suitable for several construction, agricultural and marine applications.

Suitable for marine equipment like: deck machine, winches, gearboxes.

Features & Benefits

Good protection

Valvoline Multipurpose Calcium 2 protects against rust and corrosion and is resistant against oxidation even in frequent or prolonged contact with water

Good performance

The product lubricates and protects under severe circumstances like damp and wet conditions. In the presence of water, a good lubricating film will be maintained, avoiding wash out.

Multipurpose applications

Valvoline Multipurpose Calcium 2 was developed for universal lubrication of several mechanical equipment working in wet circumstances.

Severe working conditions

The product can even be used in unfavorable working conditions like canal building or swamp lumbering or on-surface mining.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Multipurpose Calcium 2	
NLGI grade	2
Soap type	Calcium
Colour	Green
Texture	Tacky
Density @ 20°C	0,950
Application temperature °C	-30 to + 100
Dropping Point, °C	140
Oil Viscosity, mm ² /s @ 40°C	100
Oil Viscosity, mm ² /s @100°C	8,5

**This information only applies to products manufactured in the following location(s):
Europe**

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used oil and grease to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 620/01

™ Trademark of Valvoline, registered in various countries © 2017

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.